

AY-x6255

CSN SELECT™ Smart Card Readers

Datasheet



AY-K6255 AY-M6255 AY-Q6255

Introduction

The CSN SELECT™ AY-x6255 is a series of multi-credential technology contactless smart card (13.56 MHz) readers. The readers have the flexibility to read the CSN from many smart card RFID standards, including MIFARE Classic Sector read, perfect for transitioning from one technology to another. They support access by an NFC compatible Android smartphone app for use in access control system solutions.¹

The readers are UV, water, and dust resistant. The readers have a sleek, modern design and can be used comfortably in any indoor or outdoor installation environment.

General Description

The AY-x6255 reader series are built to read the CSN of the most popular smart cards in the security industry, including MIFARE sector read, as well as NFC compatible Android smartphones, and output the CSN in Wiegand or OSDP protocols.

Four individual control lines provide green LED control, red LED control, and buzzer control inputs, as well as an output for the optical wall tamper detector. AY-x6255 readers support SIA Open Supervised Device Protocol (OSDP V2) including SCP mode (Secured Channel Protocol) to let the reader connect to any controller that supports OSDP.

Main Features

- The reader settings can be configured with the CS-CCT Configuration Tool
- Supports OSDP V2 including secure channel using AES 128 bit encryption for improved security with an extended range, up to 32 addresses
- MIFARE Classic EV1 Sector Read - Compatible with ISO 14443A 1K and 4K credentials
- Supports NFC¹ technology using Rosslare BLE-ID mobile app or SDK.
- Sleek and modern design
- Tri-colored LED operation
- Optical wall tamper detection
- Multiple mounting options including micro-mullion, mullion, US gangbox and UK/Asia gangbox
- Comes with mounting template and installation kit for easy installation
- Water and dust resistant
 - IP68 for models without DIP switches
 - IP65 for models with DIP switches
- IK08 vandal resistance (without the bezel)

¹NFC-ID can be generated from the Rosslare BLE-ID app or Rosslare Mobile Credentials SDK for each NFC supported Android smartphone.

Technical Specifications

Electrical Characteristics	
Operating Voltage Range	8 to 16 VDC
Current at 12 V	AY-K/L6255: Standby: 55 mA, max: 80 mA
	AY-H/M6255: Standby: 75 mA, max: 110 mA
	AY-Q6255: Standby: 100 mA, max: 150 mA
Read Range	AY-K6255/AY-Q6255: 5 cm (2.0 in.) ¹
	AY-L6255: 7 cm (2.9 in.) ¹
	AY-H/M6255: 9 cm (3.5 in.) ¹
	NFC up to 7 cm (2.9 in.) ²
LED/Buzzer Controls	Dry Contact, N.O.
Tamper Output	Open collector, active low, max. sink current 16 mA
Credential Technology ¹	13.56MHz: ISO14443A: MIFARE Classic® EV1 / MIFRAE Classic EV1 Sector read / MIFARE Classic®, MIFARE Ultralight® Nano / MIFARE Ultralight® EV1/ MIFARE Ultralight® C, MIFARE Plus® S / MIFARE Plus® SE / MIFARE Plus® X / MIFARE Plus® EV1, MIFARE DESFire® EV1/ MIFARE DESFire® EV2, MIFARE NFC N-TAG / Card Emulation ISO14443B - China National ID ISO15693 HID®, iClass®, PicoPass, iCode, LEGIC ISO18092: SONY® FeliCa® (Hong Kong Octopus)
Communication and Controller Connection	Wiegand: 26 (default), 32, 34, 40, 56, 64, 96, 128-bits Wiegand Card + PIN Clock & Data OSDP Secure Channel V2
Maximum Cable Distance to Controller	Wiegand: 150 m (500 ft) with 18-AWG cable OSDP (RS-485): 1,200 m (4,000 ft) with 2x2 18-AWG twisted shielded cable
Environmental Characteristics	
Operating Temp. Range	-35°C to 66°C (-31°F to 150°F)
Operating Humidity Range	0 to 95% (non-condensing)
Operating Environment	UV-resistant, epoxy-potted, suitable for indoor and outdoor use <ul style="list-style-type: none"> • IP68 for models without DIP switches • IP65 for models with DIP switches
Vandal Resistance	IK08 (without the bezel)

¹Measured using a Rosslare MIFARE Classic EV1 (ISO card). Read range with other credential technologies may vary. Range also depends on electrical environment and proximity to metal.

²The NFC read range is different for different smartphones and also is affected by a variety of factors.

Physical Characteristics

Dimensions (H x W x D)	AY-K6255: 80.5 x 40.5 x 14.7 mm (3.2 x 1.6 x 0.6 in.)
	AY-L6255: 145.0 x 43.0 x 22.3 mm (5.7 x 1.7 x 0.9 in.)
	AY-H6255: 110.7 x 75.0 x 17.0 mm (4.4 x 3.0 x 0.7 in.)
	AY-M6255: 89.5 x 88.5 x 16.9 mm (3.5 x 3.5 x 0.7 in.)
	AY-Q6255: 120.0 x 76.0 x 21.5 mm (4.7 x 3.0 x 0.9 in.)
Weight	AY-K6255: 73 g (2.6 oz)
	AY-L6255: 130 g (4.6 oz)
	AY-H6255: 177 g (6.2 oz)
	AY-M6255: 167 g (5.9 oz)
	AY-Q6255: 410g (14.5 oz)

System Components: AY-x6255 are compatible with a variety of Rosslare controllers, as well as with many third-party access control systems supporting Wiegand or OSDP interfaces.

Product Warranty: 5-year limited product warranty



MIFARE and MIFARE Classic are trademarks of NXP B.V. | MIFARE and DESFire are registered trademarks of NXP B.V. | MIFARE and MIFARE Plus are registered trademarks of NXP B.V. | MIFARE and MIFARE Ultralight are registered trademarks of NXP B. V. | All product names, logos, and brands are property of their respective owners.

DISCLAIMER: The data contained within Rosslare's materials or documentation is intended to provide only general information about products available for purchase from Rosslare Enterprises Ltd. and its associated companies ("Rosslare"). Reasonable efforts have been made to ensure the accuracy of this information. However, it might contain typographic errors, inaccuracies, or omissions that may relate to product descriptions, visual pictures, specifications, and other details. All technical specifications weights, measures and colors shown, are best approximations. Rosslare can not be held responsible and assumes no legal liability for the accuracy or completeness of the information provided. Rosslare reserves the right to change, delete, or otherwise modify the information, which is represented, at any time, without any prior notice.

© 2022 Rosslare Enterprises Ltd. All rights reserved.

For more information regarding support, visit <https://support.rosslaresecurity.com>.