

ROSSLARE'S NEWEST STANDALONE BACKLIT PIN & PROXIMITY CONTROLLER, THE AC-G44, IS A COST-EFFECTIVE SOLUTION FOR INDOOR AND OUTDOOR SYSTEMS WHERE PIN AND/OR PROXIMITY CREDENTIALS ARE REQUIRED. THIS DURABLE MODEL CAN BE EASILY PROGRAMMED WITH UP TO 500 USERS ON A SINGLE DOOR.

GENERAL DESCRIPTION

For greater peace of mind, this sturdy access control unit provides three levels of security that can be assigned to as many as 500 users. The AC-G44 offers automatic mode recognition and a user-friendly setup menu, simplifying configuration and use. Extra features such as various door alarms, LED control input, and tamper detection provide extra security and flexibility.

Come rain or shine, this reader can handle the challenge, with its rugged UV-resistant housing and water-resistant enclosure for maximum durability.

The backlit keypad is clearly visible day or night, making these units ideal for residential, commercial and industrial applications.

MAIN FEATURES

- Up to 500 users can be coded using Smart enroll and delete technology
- Mounting template and installation kit are provided
- Three user levels:
 - Normal Requires single PIN code or PROX card
 - Secure Requires both PIN and PROX card
 - Master User

- Three access levels:
 - Normal
 - Bypass
 - Secure
- Suitable for Gang Box installations
- Programmable PIN code length of 4 digits to 8 digits
- Powered either by transformer (AC) or regulated power supply (DC)

PROFESSIONAL GRADE FEATURES

- Water-resistant and UV-resistant, meets IP65
- Internal buzzer
- Two inputs: REX and Auxiliary
- Two Form C, 2 Amp outputs: Lock Strike and Auxiliary
- Two tri-colored status/programming LEDs
- 10 auxiliary modes including: Door Ajar, Forced Door, Alarm Shunt, and Door Monitor
- Programmable chime and siren when using BL-D40 and '*' bell button
- Built-in optical back tamper detection



SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

PRODUCT WARRANTY	5-year Limited Product Warranty
SYSTEM COMPONENTS	The AC-G44 is compatible with the BL-D40 alarm, chime and doo bell enunciator/strobe unit, as well as with the EX-01 Push to Exit button.
 Weight 	178 g (0.39 lbs)
Dimensions (L x W x H)	135.4 x 44.2 x 28.5 mm (5.33 x 1.74 x 1.12 in.)
PHYSICAL SPECIFICATIONS	
RFI Protection	> 20 V/m up to 1000 MHz
 Operating Humidity 	0 to 95% (non-condensing)
 Operating Temperature 	-30°C to 65°C (-22°F to 150°F)
Operating Environment	Water resistant, suitable for outdoor use (IP65)
ENVIRONMENTAL SPECIFICATIONS	
Design	Epoxy potted, fully-sealed in a rugged polycarbonate enclosure. Red illuminated rubber keys. Suitable for harsh environments.
Audio/Visual	Interface for BL-D40 (bell, chime and siren enunciator) Two tri-color LED indicators, built-in sounder
 Security Modes 	Normal, Bypass, Secure
User Levels	Normal, Secure, Master
 Keypad 	2x6 keys for local programming and 4- to 8-digit PIN code entry
Capacity	500 users, dual code/card or code + card each
OPERATIONAL SPECIFICATIONS	
Proximity Card Reader	Maximum read range*: 80 mm (3.15 in.) Modulation: ASK at 125 kHz Compatible cards: All 26-bit EM cards * Measured using Rosslare Prox Card AT-R14 or equivalent. Range also depends on electrical environment and proximity to metal.
Inputs	REX: N.O. Dry Contact Auxiliary (In/Monitor): N.O. Dry Contact. 10 Programmable modes
Tamper	Optical back tamper sensor
Relay Outputs	Lock Strike: 2 A Form C, N.O. and N.C. Auxiliary: 2 A Form C, N.O. and N.C.
Input Current	Standby: 95 mA at 12 VDC Maximum: 160 mA at 12 VDC
 Operating Voltage Range 	12 to 24 VDC, from a regulated power supply 16 to 24 VAC, from a transformer

ABOUT ROSSLARE SECURITY

Rosslare Security Products, a division of Rosslare Enterprises Ltd., has been manufacturing high-quality security products since 1980. The company's three main lines – Access Control, Intrusion Detection and Guard Patrol – together with a growing product range have transformed Rosslare Security into a major worldwide force in security. Rosslare holds itself to the highest standards of customer service and manufacturing (ISO 9001:2008, ISO 14001:2004, ISO 13485:2003). The company complies with the EU Directive 2002/95/EC on Restriction of Hazardous Substances (RoHS).

Visit our website: www.rosslaresecurity.com







5505-0033101-00 Copyright © Rosslare 2012